


KING LONG

ALL-NEW
NOVA 82Y
TRANSFORMATION FOR BETTER MOBILITY





GRILLE
Chrome King Long logo which is harmonious, modern and classy



LIGHT SYSTEM
Equipped with Halogen Projector light and integrated with daytime LED lights to help enhance visibility




USEFUL SIDEVIEW MIRROR
Designed to be anti-vibration with electric adjustment and defroster



PASSENGER AREA (28 SEATER)
Wide and luxurious passenger seats
Spacious with 860mm legroom
Wide aisle, luxurious wood grain floor with anti-slip features



DRIVER FOCUS
The driver area is spacious, has clear visibility and equipped with air suspension seat



REAR-VIEW CAMERA
Infrared camera works well during the day and at night



ATTRACTIVE REAR COMBINATION LIGHTS
Integrated brake lights, turn signal and rear light



EURO 5 **WEICHAH ENGINE**
A powerful and fuel-efficient Euro 5 engine



ALUMINUM ALLOY RIM
Strong alloy rim aesthetically designed



TC MOTOR VIETNAM
Modern bus assembly plant meets national quality standards

SPECIFICATIONS
DIMENSION

Overall Dimension (L x W x H)	mm	8300 x 2480 x 3390
Wheelbase	mm	3950

WEIGHT

Curb Weight	kg	8450
Gross Vehicle Weight	kg	11820
Seat	Seat	29 (28 passenger + 1 driver)

ENGINE

Brand	WEICHAI (with European technology)	
Model	WP4.6NQ220E50 (Euro 5)	
Type	Inline 4-cylinder, Intercooler-diesel with common rail direct fuel injection	
Bore x Stroke	mm	108 x 125
Piston Displacement	cc	4580
Maximum Output Power	Ps/rpm	220 / 2300 rpm
Maximum Torque	N.m/rpm	800 / 1200 ~ 1800 rpm

TRANSMISSION

Model	FAST 6DS80T
Gear	6 Forward, 1 Reserve (manual)
Gear ratio	6.62 3.73 2.3 1.51 1 0.74 R:6.05

STEERING SYSTEM

Type	Hydraulic power steering
------	--------------------------

BRAKE SYSTEM

Brake System	Front: Disc Brake; Rear: Drum brake, with ABS
Parking Brake	Spring applied pneumatic release on rear wheels
Auxiliary Brake	Exhaust brake

SUSPENSION

Front	2 air-bellows, 2 hydraulic shock absorbers with stablizer bar
Rear	4 air-bellows, 2 hydraulic shock absorbers with stablizer bar

TIRE

Tire	Front: 9R22.5 / Rear: 9R22.5 / Tubeless
Rim	Alloy Rim 6.75 x 22.5

SPECIALITY

Maximum speed	km/h	110
Minimum turning radius	m	8.10
Fuel tank capacity	L	168
Maximum Gradeabilit	%	35.2

EQUIPMENT & ACCESSORIES

Rear view mirror	Electric rear view mirror with wide-area view (with heating demister, one longer + the other shorter)
Driver seat	Damping & adjustable driver seat (air suspension) with three-point safety belt
Passenger seat	The first row seats is equipped with 3-point seat belts, behind each seat there are Type-A and Type-C USB charging ports
Fire Extinguisher	Engine compartment: 2 x Automatic fire extinguisher. Cabin: 2 x 4kg ABC powder fire extinguisher
Luggage compartment	PVC board with aluminium chequered plate
Door	Pneumatic swing out type with remote control
Standard Equipment & Others	Reverse camera, 500GB Multimedia Player, 22" auto-folding LCD monitor

** Photos are for illustration purposes only and may differ slightly from the actual product.



29-seats layout

Dealer's information

